

BYRON POOL PAINT

PolySoft has partnered with a leading Australian swimming pool paint company, to bring you a range of high quality pool paint colours that are complementary to PolySoft Surfacing. We would like to introduce you to our Byron Pool Paint Range.



POLYSOFT
FLEXIBLE SEAMLESS PAVING



BYRON POOL PAINT is the premium choice for all new pool and aquatic facilities and can also be used to achieve a beautiful luxury finish in older pools. Byron Pool Paint is suited to application over both old and new cement render, fibreglass, marble sheen, pebble crete and sound existing epoxy finishes.

Byron Pool Paint provides a smooth, hard surface which is simple to maintain. Byron Pool Paint colours are formulated to the highest technical standards and feature a durable luxury finish with improved resistance to chalking, salt water and pool chlorination chemicals. It is algae controlled and safe for use with fish and mammals after proper surface conditioning.





Colour Range —



Regency White



New Riversand



Emerald Green



Pond Green



Opaline



Brook Green [CR]




Aquamist [CR]



Atlantis*



White [CR]



Whitsunday



Lagoon



Turquoise*



New Jacaranda



Crestwood



Pacific Blue [CR]



Adriatic [CR]



Tahitian



Misty Blue



Mid Blue



Devonport*



Serenity



Platinum



Slate* [CR]



Deep Ocean*

*Stock Designer Colours – premium charges apply.

Disclaimer: The samples in this colour card are as near to the actual colours as the printing process permits. Actual colours vary from this colour card and from batch to batch. Prospective users and specifiers MUST satisfy themselves as to the suitability of coating and colour prior to application. Colour samples may be made available for this purpose; charges apply.



Black [CR]



Coverage

Approximately 20–25 m²/3.5L kit per coat for best results, dependant on surface type and quality. A 200–400 µm DFT system is recommended. Service life is directly proportional to coating thickness. For commercial applications, contact *Byron Pool Paint*. A minimum application of 2 colour coats (preferably 3) of Byron Pool Paint is recommended for best service life. For extremely porous surfaces, *Byron Pool Paint Primer Sealer* is recommended as a first coat. An average size pool (9x4.5m x 1.5m average depth; approx 80m² or 60,000L) requires approximately 5–8x3.5L colour kits for a 2 coat finish and 7–10 kits for a 3 coat finish. Approximately 5m²/L per coat, depending on surface type and porosity. A minimum of 3 coats recommended; 4 coats are preferred for best service life.

Colours

Byron Pool Paint is available in 20 standard and 5 stock Designer Colours. Other Designer Colours, available by special arrangement, include over 200 Aust. Std. [AS 2700] colours.

Should be applied by brush and roller only over a properly prepared substrate. Refer to the relevant Application Guide for specific substrate types if considering DIY application.

Application

Should be applied by brush and roller only over a properly prepared substrate. Refer to the relevant Application Guide for specific substrate types if considering DIY application.

Pool Water Chemistry

MAINTAIN: • pH between 7.6 and 7.8 • TOTAL ALKALINITY between 140–160 ppm for light colours, 160–180 ppm for darker colours. • CALCIUM HARDNESS of 250–300 ppm
• CHLORINE LEVELS at a minimum consistent with good hygiene; <3.0 for Epoxy
• MINIMISE USE OF ACID where possible. • BRUSH DOWN pool surfaces every 4–6 weeks over the Swimming season to maintain a coating of good integrity and thus improve service life.

It is good practice to continue to brush down every 6–8 weeks in the off-season.

The above advice is a general guide only. Application Guides specific to your pool surfaces may be obtained from *PolySoft Pty Ltd*.

PLEASE NOTE: all pools vary with respect to surface type, texture and integrity and this will influence the finished coating. Also, climatic and/or weather conditions prior to, during and after the application of *Byron Pool Paint* will affect the finished coating. These variables MUST be taken into account by the user or applicator

PolySoft Pty Ltd
1a Bonz Place, Seven Hills
Australia NSW 2147
+61 296 24 1388
www.polysoftsurfaces.com
info@polysoft.com.au

POLYSOFT

FLEXIBLE SEAMLESS PAVING